



MODEL	kw		(Kg)	Kaldırma Ağırlığı(Tn)	Kapasite (m3)	Maximum Basınç(bar)	Kapanış Süresi(sn)		Ölçüler(mm)				
	380V50Hz	440V60Hz					380V50Hz	440V60Hz	A	B	C	D	E
NG15.0-1250	15.0	18.0	1360	3.6	1.25	180	10	--	2100	2010	1640	1950	1400
NG 15.0-1600			1520	4.4	1.6	180	10	--	2120	2080	1740	2080	1540
NG 18.5-2000	18.5	22.0	1870	5.5	2.0	180	12	--	2320	2200	1900	2240	1700
NG 18.5-2500			2030	6.6	2.5	180	12	--	2360	2320	2080	2460	1860
NG 22.0-3000	22.0	26.0	3080	8.5	3.0	200	15	--	2960	2890	2200	2710	1960
NG 22.0-4000			3560	10.8	4.0	200	15	--	3050	2950	2200	2800	2300
NG 30.0-5000	30.0	35.0	4860	13.9	5.0	200	20	--	3380	3070	2520	3020	2300
NG 30.0-6300			5180	16.5	6.3	200	20	--	3500	3100	2670	3240	2500
NG 30.0-8000			6650	21.1	8.0	200	23	--	3500	3220	2920	3400	2640
NG .0-9000	37.0	44.0	8160	24.4	9.0	200	23	--	3760	3300	3050	3700	2940
NG 37.0-10000			8350	26.4	10.0	200	25	--	3760	3300	3050	3700	3250
NG 37.0-11000			8520	28.3	11.0	200	25	--	3760	3300	3050	3700	3560
NG 45.0-12000	45.0	54.0	9880	31.5	12.0	220	25	--	4100	3820	3280	3960	3430
NG 45.0-13000			10210	33.6	13.0	220	25	--	4100	3820	3280	3960	3700
NG 45.0-14000			10500	35.7	14.0	220	25	--	4100	3820	3280	3960	3980
NG 55.0-15000	55.0	66.0	13720	40.7	15.0	220	25	--	4420	4120	3560	4210	3650
NG 55.0-16500			14250	44.0	16.5	220	25	--	4420	4120	3560	4210	4120
NG 55.0-18000			14710	47.1	18.0	220	25	--	4580	4130	3780	4420	4200